

POLY-TECT

CLEARCOAT PROTECTANT

DESCRIPTION

This polymer protectant offers new technology for clearcoat sealers. This product uses a proprietary non-silicone polymer fluid, fortified with UV inhibitor that provides exceptional shine that customers WILL notice. Once applied, this polymer fluid will not evaporate like traditional mineral seal oil based drying agents, thus providing substantially longer water and UV protection.

USAGE INSTRUCTIONS

This product is ideally applied under low pressure application in tunnel and in-bay automatic settings. Begin application at 275-475:1 (4-6 drops). Product can be applied under high pressure. When doing so be sure to push the dilution further to 650-950:1 (2-3 drops). Watch carefully not to overuse as it can reverse the drying effect. Product can also be applied in self-serve settings, but be sure to consult with your sales representative first.

FEATURES

- UV protection
- Uses non-silicone polymer fluids
- Enhance shine and protection
- Great eucalyptus-mint fragrance

SIZES AVAILABLE

5-gallon pails Code: 10-50118-005
15-gallon drums Code: 10-50118-015
30-gallon drums Code: 10-50118-030
55-gallon drums Code: 10-50118-055

SPECIFICATIONS

COLOR: YELLOW
FRAGRANCE: EUCALYPTUS MINT
FOAM: NONE
PH: 6-7

Drop Count (Titration)	Oz/Gal of water	Ratio to 1
2	.13	959
3	.20	639
4	.27	479
5	.33	383
6	.40	319
7	.47	273
8	.53	239
9	.60	212
10	.67	191
11	.73	174
12	.80	159
13	.87	147



**ANYTHING
BUT ORDINARY**