



# LIQUID TOWEL

## Safety Data Sheet

Revision Date: 1/4/2021

### SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

#### 1.1 Product Identifier

Trade Name LIQUID TOWEL  
Product Form Mixture  
Product Code 11-17420

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of Product Drying Agent

#### 1.3 Details of the Supplier of the safety data sheet

ChemQuest Inc.  
21365 Hamburg Ave.  
Lakeville, MN 55024  
(877)437-3478  
infocq@chemquestinc.com

#### 1.4 Emergency telephone number

Emergency Number ChemTrec 1-800-424-9300

### SECTION 2: Hazards Identification

#### 2.1 Classification of the substance

##### Classification

<u>Hazard Code</u>	<u>Hazard Class</u>	<u>Hazard Category</u>
H226	Flammable liquids	3
H304	Aspiration hazard	1
H315	Skin corrosion/irritation	2
H317	Sensitization, skin	1
H318	Serious eye damage/eye irritation	1
H361	Reproductive toxicity	2
H401	Hazardous to the aquatic environment, acute toxicity	2
H411	Hazardous to the aquatic environment, chronic toxicity	2

HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFEETY PRACTICES

#### 2.2 Label Elements

##### GHS-US Labeling

##### Hazard Pictograms (GHS-US)



Signal Word (GHS-US): **Danger**

##### Hazard Statements (GHS-US):

H226: Flammable liquid and vapor  
H304: May be fatal if swallowed and enters airways  
H315: Causes skin irritation  
H317: May cause allergic skin reaction  
H318: Causes serious eye damage  
H361: Suspected of damaging fertility or the unborn child  
H401: Toxic to aquatic life  
H411: Toxic to aquatic life with long lasting effects

##### Precautionary Statements (GHS-US):

P201: Obtain special instructions before use

# LIQUID TOWEL

## Safety Data Sheet

P202: Do not handle until all safety precautions have been read and understood

P210: Keep away from heat/sparks/open flames/hot surfaces. -No smoking.

P233: Keep container tightly closed

P240: Ground/bond container and receiving equipment

P241: Use explosion-proof electrical/ventilating/lighting/.../equipment

P242: Use only non-sparking tools

P243: Take precautionary measures against static charge

P261: Avoid breathing dust/fumes/gas/mist/spray

P264: Wash thoroughly after handling

P272: Contaminated work clothing should not be allowed out of the workplace

P273: Avoid release into the environment

P280: Wear protective gloves/protective clothing/eye protection/face protection

P321: Specific treatment (see section 4)

P331: Do NOT induce vomiting

P362: Take off contaminated clothing and wash before reuse

P391: Collect spillage

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P302+P352: IF ON SKIN: Wash with soap and water

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

P308+P313: IF exposed or concerned: Get medical advice/attention

P333+P313: If skin irritation or a rash occurs: Get medical advice/attention

P370+P378: In case of fire: See section 5 for extinction

P403+P235: Store in a well ventilated place. Keep cool

P405: Store locked up

P501: Dispose of contents/container in accordance with local, state and federal authorities.

### 2.3 Other Hazards

No additional information available

### 2.4 Unknown acute toxicity (GHS-US)

No Data Available

## SECTION 3: Composition/Information on Ingredients

### 3.1 Substance

Not applicable

### 3.2 Mixture

<u>Ingredient Name</u>	<u>CAS #</u>	<u>Composition</u>
Water	7732-18-5	50-75%
Distillates, petroleum, hydrotreated middle	64742-46-7	10-20%
Quaternary Ammonium Compounds, DiCocoalkyl, Dimethyl, Chlorides	61789-77-3	5-10%
2-butoxyethanol	111-76-2	5-10%
Amines, C14-18; C16-18-Unsat., Alkyl, Ethoxylated	68155-39-5	1-5%
2-Propanol	67-63-0	1-5%

## SECTION 4: First Aid Measures

### 4.1 Description of first aid measures

# LIQUID TOWEL

## Safety Data Sheet

First-Aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-Aid after inhalation	IF INHALED. Use artificial respiration and oxygen if needed. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If irritation persists, seek medical attention.
First-Aid after skin contact	IF ON SKIN. Wash with soap and water. IF ON SKIN (or hair). Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately rinse with plenty of water (for at least 15 minutes).
First-Aid after eye contact	IF IN EYES. Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). If irritation persists, seek medical attention.
First-Aid after ingestion	IF SWALLOWED. Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting. Dilute stomach contents by drinking water. If vomiting occurs spontaneously, keep head below hips to prevent breathing vomit into lungs. Call physician immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms/injuries	May be fatal if swallowed and enters airways. Causes skin irritation. May cause allergic skin reaction. Causes serious eye damage. Suspected of damaging fertility or the unborn child.
Symptoms/injuries after inhalation	May be fatal if swallowed and enters airways.
Symptoms/injuries after skin contact	Causes skin irritation. May cause allergic skin reaction.
Symptoms/injuries after eye contact	Causes serious eye damage.
Symptoms/injuries after ingestion	May be fatal if swallowed and enters airways.
Chronic symptoms	No data available.

### 4.3 Indication of immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting Measures

### 5.1 Extinguishing media

Suitable Extinguishing Media Alcohol resistant foam. Carbon dioxide. Dry powder. Do Not Use Water Spray.

### 5.2 Special hazards arising from the substance or mixture

Fire Hazard	Flash Point 135 F (Closed Cup). However, this product did not sustain combustibility per ASTM 4206, Standard Test Method for Sustained Burning of Liquid Mixtures Using the Small Scale Open-Cup Apparatus.
Explosion Hazard	The product is not explosive.
Reactivity	The product is not reactive under normal conditions.

### 5.3 Special hazards arising from the substance or mixture

Firefighting instructions	Do not dispose of fire-fighting water in the environment. Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers.
Protection during firefighting	Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

General measures Ventilate area. Avoid breathing vapors, mist or gas. Spill should be handled by trained clean-up crews. Use grounding/bonding and non-sparking tools. Eliminate all ignition sources. For personal protection see Section 8.

#### 6.1.1 For non-emergency personnel

Protective equipment	Wear Protective equipment as described in Section 8.
Emergency procedures	Contain the spill. Do not let product enter drains. Remove unnecessary personnel.

#### 6.1.2 For emergency responders

Protective equipment	Wear Protective equipment as described in Section 8.
----------------------	--

### 6.2 Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

# LIQUID TOWEL

## Safety Data Sheet

### 6.3 Methods and material for containment and cleaning up

For containment	Prevent entry to sewers and public waters. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	Use grounding/bonding and non-sparking tools. Eliminate all ignition sources. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

### 6.4 reference to other sections

No additional information available.

## SECTION 7: Handling and Storage

### 7.1 Precautions for safe handling

Precautions for safe handling	Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks and open flame. Store in cool well ventilated area. Ground and bond all containers when pouring or transferring liquid. Keep container closed when not in use. Use only with adequate ventilation. Wear proper safety equipment including chemically resistant gloves and safety glasses or goggles. Wash thoroughly after handling. Do not breathe mist or vapor. Do not get in eyes. Avoid prolonged or repeated contact with skin. Do not swallow.
-------------------------------	---

### 7.2 Conditions for safe storage, including and incompatibilities

Storage conditions	Store locked up. Store in approved containers only. Keep container in a cool, well ventilated place away from heat sources and incompatible materials (See Section 10.5). Keep container tightly closed.
--------------------	--

### 7.3 Specific end uses

No additional information

## SECTION 8: Exposure Controls/Personal Protection

### 8.1 control parameters

No OSHA and ACGIH PEL's or TLV's for the listed ingredients of this product unless listed stated below:

2-Butoxyethanol, CAS # 111-76-2			
OSHA PEL (TWA)	OSHA PEL (STEL)	OSHA PEL (Ceiling)	ACGIH-TLV
50 ppm	Not Established	Not Established	20 ppm (TWA)

Isopropyl alcohol, CAS # 67-63-0			
OSHA PEL (TWA)	OSHA PEL (STEL)	OSHA PEL (Ceiling)	ACGIH-TLV
400 ppm	Not Established	Not Established	200 ppm (TWA),400 ppm(STEL)

### 8.2 Exposure Controls

Personal protective equipment	Chemical resistant gloves. Protective clothing. Safety glasses or goggles
Hand protection	Chemical resistant gloves.
Eye protection	Safety glasses or goggles.
Skin and body protection	Wear long sleeves. Wear suitable protective clothing.
Respiratory protection	Where excessive vapor, mist, or dust may result, use approved respiratory protection equipment.

## SECTION 9: Physical and Chemical Properties

### 9.1 Information on basic physical and chemical properties

Appearance	Tinted Liquid
Color	Blue
Odor	Mint
Odor threshold	No data available
pH	8.5

# LIQUID TOWEL

## Safety Data Sheet

Relative Evaporation rate (butyl)	No data Available
Melting point	No data Available
Freezing point	No data Available
Boiling point	No data Available
Flash point	135 °F (Closed Cup)
Self ignition point	No data Available
Decomposition temperature	No data Available
Flammability (solid, gas)	No data Available
Vapor pressure	No data Available
Relative vapor density at 20° C	No data Available
Relative Density	0.954 g/ml
Solubility	Water soluble
Log Pow	No data Available
Log Kow	No data Available
Viscosity: Kinematic	No data Available
Viscosity: dynamic	No data Available
Explosive properties	No data Available
Oxidizing properties	No data Available
Explosive Limits	No data Available

### 9.2 Exposure Controls

No additional information available

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2 Chemical Stability

Stable under recommended handling and storage conditions (see section 7).

### 10.3 Possibility of hazardous reactions

None Known

### 10.4 Conditions to avoid

Sparks. Heat. Open flame. Sun Light

### 10.5 Incompatible Materials

Avoid contact with: bases, amines, ammonia, strong acids, acid chlorides, and strong oxidizers

### 10.6 Hazardous decomposition products

Thermal decomposition can result in: aldehydes, hydrocarbons, and carbon oxides

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Oral LD50: > 2000 mg/kg (rat) Calculated

Dermal LD50: > 2000 mg/kg (rabbit) Calculated

Inhalation LD50: > 5 mg/l (Dust/mist (Rat)) Calculated

Skin Corrosion/irritation Causes skin irritation

Serious eye damage/irritation Causes serious eye damage

Respiratory or skin sensitization May cause allergic skin reaction

Germ cell mutagenicity Not Classified

Carcinogenicity Not Classified

Reproductive toxicity Suspected of damaging fertility or the unborn child

Specific organ toxicity single exposure Not Classified

Specific organ toxicity repeated exposure Not Classified

# LIQUID TOWEL

## Safety Data Sheet

Aspiration hazard	May be fatal if swallowed and enters airways
Symptoms/injuries after inhalation	See Section 4
Symptoms/injuries after skin contact	See Section 4
Symptoms/injuries after eye contact	See Section 4
Symptoms/injuries after ingestion	See Section 4
Chronic symptoms	Not Classified

### SECTION 12: Ecological information

#### 12.1 Toxicity

No Data

#### 12.2 Persistence and degradability

No Data

#### 12.3 Bioaccumulative potential

No Data

#### 12.4 Mobility in soil

No Data

#### 12.5 Other adverse effect

No Data

### SECTION 13: Disposal Considerations

#### 13.1 Waste Treatment methods

Waste treatment methods Do not discharge to public wastewater systems without permit of pollution control authorities.  
No discharge to surface waters is allowed without NPDES permit.

Waste disposal recommendations Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released to the environment.

### SECTION 14: Transportation information

#### 14.1 UN number, proper shipping name, class and packaging groups.

Domestic Ground Non-Bulk Shipments

NOT DOT REGULATED

#### 14.2 Additional information

Not available

### SECTION 15: Regulatory Information

#### 15.1 Federal regulations

**TSCA Inventory:** The components of this product are listed.

**SARA 311/312 Hazard category (40 CFR 370.2):** Acute and chronic health hazard, fire hazard.

**SARA 313 Toxic Release Reporting (40CFR Part 372):** 2-Propanol , CAS# 67-63-0, 1-5% by wt./ 2-butoxyethanol, CAS# 111-76-2, 5-10% by wt.

**SARA 302 EHS Emergency Planning (40CFR Part 355):** No listed substance known over 1.0% or over 0.1% that are carcinogenic.

**SARA 304 EHS Emergency Planning (40CFR Part 355):** No listed substance known over 1.0% or over 0.1% that are carcinogenic.

**CERCLA Section 102-103 HS Released Reporting (40 CFR part 302-102a):** 2-butoxyethanol, CAS# 111-76-2, RQ no listed value, see 50 Federal Register 13456 for RQ lbs.

#### 15.2.1 International regulations

No Data

#### 15.2.2 National regulations

No Data

#### 15.3 State Regulations

##### California Prop. 65

Approximate quantities by weight

# LIQUID TOWEL

## Safety Data Sheet

---

- Ethylene glycol (ingested)/ developmental/ CAS# 107-21-1/ Trace
- Methyl chloride/ developmental / CAS# 74-87-3/ Trace
- Methyl chloride [Basis for listing changed effective March 7, 2014]/ male / CAS# 74-87-3/ Trace

### New Jersey Right to Know

Approximate quantities by weight

- 2-BUTOXY ETHANOL/ CAS# 111-76-2/ 5-10% by wt.
- ISOPROPYL ALCOHOL/ CAS# 67-63-0/ 1-5% by wt.
- ETHYLENE GLYCOL/ CAS# 107-21-1/ Trace
- METHYL CHLORIDE/ CAS# 74-87-3/ Trace
- DIETHYL PHTHALATE/ CAS# 84-66-2/ Trace

<b>SECTION 16: Other Information</b>
--------------------------------------

Other information	None
NFPA	
NFPA Health Hazard	2
NFPA Fire Hazard	2
NFPA Reactivity	0
HMIS	
Health	2
Flammability	2
Physical	0
Personal Protection	X

The information contained herein has been compiled from sources believed to be reliable and is accurate to the best of our knowledge at this date. It is provided without warranty, expressed or implied, as to the results of use of this information or to the product to which it relates. Recipient assumes all responsibility for the use of this information and the use, storage, or disposal of the product, including any resultant personal injury or property damage.